

MP ROTATOR®

Radius: **8' to 35'**

0.4
in/hr

The MP Rotator ozzle is the most trusted high-efficiency solution on the market, offering up to 30% water savings over traditional spray nozzles.

KEY BENEFITS

- Low precipitation rate of approximately 0.4 in/hr — lowest in the industry
- Automatic matched precipitation for simplified irrigation design and flexibility
- Double-pop feature protects the nozzle from external debris
- High distribution uniformity for a healthy landscape with maximum water efficiency

ADDITIONAL FEATURES

- Wind-resistant, multi-stream technology prevents misting
- For vandal resistance, the arc is adjustable only when the MP Rotator is running
- Removable filter screen prevents nozzle from clogging
- Color-coded for easy identification

OPERATING SPECIFICATIONS

- Radius reduction up to approximately 25% on all models
- Recommended operating pressure: 40 PSI
- Minimum radius setting achieved at 30 PSI
- Warranty period: 3 years

OPTIONS

- Pair with Pro-Spray® PRS40 Sprinkler Body for pressure regulation to 40 PSI for nominal radius settings
- Pair with Pro-Spray PRS30 Sprinkler Body for pressure regulation to 30 PSI for minimum radius settings

MP1000: 8' to 15' radius



MP1000-90
90° to 210°

MP1000-210
210° to 270°

MP1000-360
360°

MP2000: 13' to 21' radius



MP2000-90
90° to 210°

MP2000-210
210° to 270°

MP2000-360
360°

MP3000: 22' to 30' radius



MP3000-90
90° to 210°

MP3000-210
210° to 270°

MP3000-360
360°

MP3500: 31' to 35' radius








MP3500-90
90° to 210°

MP ROTATOR - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
MP1000-90 = 8' to 15' radius, adjustable from 90° to 210°	(blank) = No option HT = Male threaded version <i>(Not available in 3500 and 1000-210)</i>
MP1000-210 = 8' to 15' radius, adjustable from 210° to 270°	
MP1000-360 = 8' to 15' radius, 360°	
MP2000-90 = 13' to 21' radius, adjustable from 90° to 210°	
MP2000-210 = 13' to 21' radius, adjustable from 210° to 270°	
MP2000-360 = 13' to 21' radius, 360°	
MP3000-90 = 22' to 30' radius, adjustable from 90° to 210°	
MP3000-210 = 22' to 30' radius, adjustable from 210° to 270°	
MP3000-360 = 22' to 30' radius, 360°	
MP3500-90 = 31' to 35' radius, adjustable from 90° to 210°	
MPLCS-515 = Left corner strip, 5' x 15'	
MPRCS-515 = Right corner strip, 5' x 15'	
MPSS-530 = Side strip, 5' x 30'	
MP-CORNER = 8' to 15' radius, adjustable from 45° to 105°	

MP ROTATOR PERFORMANCE DATA

Arc	Pressure PSI	MP1000 Radius: 8' to 15' Adjustable Arc and Full-Circle ● Maroon: 90° to 210° ● Lt. Blue: 210° to 270° ● Olive: 360°					MP2000 Radius: 13' to 21' Adjustable Arc and Full-Circle ● Black: 90° to 210° ● Green: 210° to 270° ● Red: 360°					MP3000 Radius: 22' to 30' Adjustable Arc and Full-Circle ● Blue: 90° to 210° ● Yellow: 210° to 270° ● Gray: 360°				
		Radius ft.	Flow GPM	Flow GPH	Precip in/hr ■ ▲	Radius ft.	Flow GPM	Flow GPH	Precip in/hr ■ ▲	Radius ft.	Flow GPM	Flow GPH	Precip in/hr ■ ▲			
90° 	25	--	--	--	--	17	0.34	20.4	0.45	0.52	25	0.71	42.6	0.44	0.51	
	30	12	0.17	10.2	0.45	0.52	18	0.38	22.8	0.45	0.52	27	0.76	45.6	0.40	0.46
	35	13	0.19	11.4	0.43	0.50	19	0.40	24.0	0.43	0.49	28	0.82	49.2	0.40	0.46
	40	14	0.21	12.6	0.41	0.48	20	0.43	25.8	0.41	0.48	30	0.86	51.6	0.37	0.42
	45	14	0.23	13.8	0.45	0.52	21	0.46	27.6	0.40	0.46	30	0.90	54.0	0.39	0.44
	50	15	0.25	15.0	0.43	0.49	21	0.47	28.2	0.41	0.47	30	0.95	57.0	0.41	0.47
180° 	25	--	--	--	--	16	0.6	36.0	0.45	0.52	25	1.44	86.4	0.44	0.51	
	30	12	0.34	20.4	0.45	0.52	17	0.64	38.4	0.43	0.49	27	1.58	94.8	0.42	0.48
	35	13	0.38	22.8	0.43	0.50	18	0.71	42.6	0.42	0.49	28	1.70	102.0	0.42	0.48
	40	14	0.42	25.2	0.41	0.48	19	0.77	46.2	0.41	0.47	30	1.82	109.2	0.39	0.45
	45	14	0.44	26.4	0.43	0.50	20	0.85	51.0	0.41	0.47	30	1.93	115.8	0.41	0.48
	50	15	0.50	30.0	0.43	0.49	21	0.91	54.6	0.40	0.46	30	2.04	122.4	0.44	0.50
210° 	25	--	--	--	--	16	0.72	43.2	0.46	0.54	25	1.68	100.8	0.44	0.51	
	30	12	0.40	24.0	0.46	0.53	17	0.75	45.0	0.43	0.49	27	1.84	110.4	0.42	0.48
	35	13	0.45	27.0	0.44	0.51	18	0.81	48.6	0.41	0.48	28	1.99	119.4	0.42	0.48
	40	14	0.49	29.4	0.41	0.48	19	0.86	51.6	0.39	0.45	30	2.12	127.2	0.39	0.45
	45	14	0.51	30.6	0.43	0.50	20	0.91	54.6	0.38	0.43	30	2.25	135.0	0.41	0.48
	50	15	0.57	34.2	0.42	0.48	21	0.98	58.8	0.37	0.42	30	2.37	142.2	0.43	0.50
270° 	25	--	--	--	--	16	0.87	52.2	0.44	0.50	25	2.19	131.4	0.45	0.52	
	30	12	0.48	28.8	0.43	0.49	17	0.95	57.0	0.42	0.49	27	2.37	142.2	0.42	0.48
	35	13	0.53	31.8	0.40	0.46	18	1.03	61.8	0.41	0.47	28	2.55	153.0	0.42	0.48
	40	14	0.63	37.8	0.41	0.48	19	1.10	66.0	0.39	0.45	30	2.73	163.8	0.39	0.45
	45	14	0.67	40.2	0.44	0.51	20	1.17	70.2	0.38	0.43	30	2.89	173.4	0.41	0.48
	50	15	0.72	43.2	0.41	0.47	21	1.23	73.8	0.36	0.41	30	3.06	183.6	0.44	0.50
360° 	25	--	--	--	--	16	1.20	72.0	0.45	0.52	25	2.88	172.8	0.44	0.51	
	30	12	0.69	41.4	0.46	0.53	17	1.28	76.8	0.43	0.49	27	3.15	189.0	0.42	0.48
	35	13	0.77	46.2	0.44	0.51	18	1.37	82.2	0.41	0.47	28	3.40	204.0	0.42	0.48
	40	14	0.84	50.4	0.41	0.48	19	1.48	88.8	0.39	0.46	30	3.64	218.4	0.39	0.45
	45	14	0.88	52.8	0.43	0.50	20	1.57	94.2	0.38	0.44	30	3.86	231.6	0.41	0.48
	50	15	0.98	58.8	0.42	0.48	21	1.68	100.8	0.37	0.42	30	4.07	244.2	0.44	0.50
55	15	1.01	60.6	0.43	0.50	21	1.74	104.4	0.38	0.44	30	4.27	256.2	0.46	0.53	

Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Hunter Pro-Spray PRS40 pressure-regulated at 40 PSI.

Works best with Pro-Spray PRS40






Compatible with:



Pro-Spray PRS40

MP ROTATOR PERFORMANCE DATA

MP3500
 Radius: 31' to 35'
 Adjustable Arc
 ● Light Brown: 90°

Arc	Pressure PSI	Radius ft.	Flow GPM	Flow GPH	Precip in/hr	
					■	▲
90° 	25	33	1.04	62.4	0.37	0.42
	30	34	1.13	67.8	0.38	0.43
	35	34	1.21	72.6	0.40	0.47
	40	35	1.28	76.8	0.40	0.46
	45	35	1.38	82.8	0.43	0.50
	50	35	1.43	85.8	0.45	0.52
180° 	25	33	2.21	132.6	0.39	0.45
	30	34	2.24	134.4	0.37	0.43
	35	34	2.65	159.0	0.44	0.51
	40	35	2.86	171.6	0.45	0.52
	45	35	3.10	186.0	0.49	0.56
	50	35	3.21	192.6	0.50	0.58
210° 	25	33	2.59	155.4	0.39	0.45
	30	34	2.84	170.4	0.41	0.47
	35	34	3.08	184.8	0.44	0.51
	40	35	3.29	197.4	0.44	0.51
	45	35	3.54	212.4	0.48	0.55
	50	35	3.76	225.6	0.51	0.59
55	35	3.94	236.4	0.53	0.61	




MP3500



Bold = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40, pressure-regulated spray body at 40 PSI.

MP ROTATOR PERFORMANCE DATA

- **MPLCS-515**: Ivory, MP Left Corner Strip
- **MPRCS-515**: Copper, MP Right Corner Strip
- **MPSS-530**: Brown, MP Side Strip

	Pressure PSI	Radius ft.	Flow GPM	Flow GPH
MP Left Corner Strip 	30	4 x 14	0.19	11.4
	35	5 x 15	0.21	12.6
	40	5 x 15	0.22	13.2
	45	5 x 15	0.23	13.8
	50	6 x 16	0.25	15.0
MP Right Corner Strip 	55	6 x 16	0.26	15.6
	30	4 x 14	0.19	11.4
	35	5 x 15	0.21	12.6
	40	5 x 15	0.22	13.2
	45	5 x 15	0.23	13.8
MP Side Strip 	50	6 x 16	0.25	15.0
	55	6 x 16	0.26	15.6
	30	4 x 28	0.38	22.8
	35	5 x 30	0.41	24.6
	40	5 x 30	0.44	26.4
	45	5 x 30	0.47	28.2
	50	6 x 32	0.49	29.4
	55	6 x 32	0.51	30.6

MP Strips



MPLCS-515
Left Corner Strip
5' x 15'



MPRCS-515
Right Corner Strip
5' x 15'



MPSS-530
Side Strip
5' x 30'



Bold = Recommended pressure
 Notes: To match the precipitation rate of Standard MP Rotator models, use single-row or triangular spacing. To match the MP800, use rectangular spacing.

See precipitation rate calculation.

MP ROTATOR PERFORMANCE DATA

MP Corner

Radius: 8' to 15'
Adjustable Arc

● Turquoise: 45° to 105°

Arc	Pressure PSI	Radius ft.	Flow GPM	Flow GPH
45°	25	--	--	--
	30	12	0.17	10.2
	35	13	0.18	10.8
	40	14	0.19	11.4
	45	14	0.21	12.6
	50	14	0.22	13.2
	55	15	0.23	13.8
90°	25	11	0.31	18.6
	30	12	0.34	20.4
	35	13	0.36	21.6
	40	14	0.39	23.4
	45	14	0.41	24.6
	50	15	0.43	25.8
	55	15	0.46	27.6
105°	25	11	0.36	21.6
	30	12	0.39	23.4
	35	13	0.42	25.2
	40	14	0.45	27.0
	45	14	0.48	28.8
	50	15	0.51	30.6
	55	15	0.53	31.8

Bold = Recommended pressure

MP Corner



MP-CORNER

Corner
8' to 15'

Male Threaded



MP-HT

Male Threaded

MP Accessories



MPTOOL

Adjusts all MP Rotator
Nozzles



MPSTICK

Snaps onto any length of
1" PVC to allow standing
adjustment. *PVC pipe not
included.*

MP Corner



MP Tool for easy adjustments

