

## PRO ADJUSTABLE NOZZLES

Choose Pro Adjustable Nozzles for optimal landscape coverage in any setting.

### Key Benefits

- Adjustable from 0° to 360° for maximum design flexibility
- Strong edges for a defined pattern with better wind resistance
- Easy-grip top for simple adjustment
- Large water droplets minimize misting with better uniformity

### Additional Features

- Matched precipitation rate on each nozzle from 8A to 17A
- Color-coded for easy field identification
- Even distribution results in better coverage

### Operating Specifications

- Recommended operating pressure: 30 PSI
- Warranty period: 2 years
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI



Radius: 4' to 17'



**4A**  
Radius: 4'



**6A**  
Radius: 6'



**8A**  
Radius: 8'



**10A**  
Radius: 10'



**12A**  
Radius: 12'



**15A**  
Radius: 15'



**17A**  
Radius: 17'

<b>Model</b>	<b>Description</b>
4A	4' radius adjustable arc nozzle
6A	6' radius adjustable arc nozzle
8A	8' radius adjustable arc nozzle
10A	10' radius adjustable arc nozzle
12A	12' radius adjustable arc nozzle
15A	15' radius adjustable arc nozzle
17A	17' radius adjustable arc nozzle

## PRO ADJUSTABLE NOZZLE PERFORMANCE DATA

### 4A & 6A

Arc	Pressure	Radius	Flow	Precip in/hr		Radius	Flow	Precip in/hr	
	PSI			ft	GPM			■	▲
45°	20	3	0.10	7.29	8.42	5	0.15	4.19	4.84
	25	3	0.11	7.12	8.22	5	0.17	4.36	5.03
	30	4	0.13	6.26	7.22	6	0.18	3.85	4.45
	35	4	0.14	6.11	7.06	6	0.18	3.55	4.10
	40	4	0.16	6.36	7.35	6	0.19	3.57	4.12
90°	20	3	0.19	6.93	8.00	5	0.30	4.19	4.84
	25	3	0.20	6.47	7.47	5	0.34	4.49	5.18
	30	4	<b>0.22</b>	<b>8.29</b>	<b>6.11</b>	6	<b>0.37</b>	<b>3.96</b>	<b>4.57</b>
	35	4	0.24	5.24	6.05	6	0.38	3.75	4.32
	40	4	0.25	4.97	5.74	6	0.40	3.76	4.34
120°	20	3	0.28	7.65	8.84	5	0.37	3.88	4.48
	25	3	0.30	7.28	8.40	5	0.38	3.76	4.35
	30	4	0.34	6.14	7.09	6	0.44	3.53	4.08
	35	4	0.36	5.81	6.71	6	0.46	3.40	3.93
	40	4	0.37	5.52	6.37	6	0.48	3.38	3.91
180°	20	3	0.34	6.20	7.16	5	0.50	3.49	4.03
	25	3	0.38	6.15	7.10	5	0.54	3.56	4.12
	30	4	<b>0.45</b>	<b>5.41</b>	<b>6.25</b>	6	<b>0.60</b>	<b>3.21</b>	<b>3.70</b>
	35	4	0.46	5.02	5.80	6	0.64	3.15	3.64
	40	4	0.48	4.77	5.51	6	0.68	3.20	3.69
240°	20	3	0.58	7.93	9.15	5	0.73	3.82	4.42
	25	3	0.62	7.52	8.68	5	0.78	3.86	4.46
	30	4	0.68	6.14	7.09	6	0.88	3.53	4.08
	35	4	0.74	6.06	6.99	6	0.92	3.40	3.93
	40	4	0.80	5.97	6.89	6	1.02	3.60	4.15
270°	20	3	0.62	7.53	8.70	5	0.88	4.10	4.73
	25	3	0.66	7.12	8.22	5	0.98	4.31	4.98
	30	4	<b>0.73</b>	<b>5.86</b>	<b>6.76</b>	6	<b>1.10</b>	<b>3.92</b>	<b>4.53</b>
	35	4	0.78	5.67	6.55	6	1.15	3.78	4.36
	40	4	0.84	5.57	6.43	6	1.20	3.76	4.34
360°	20	3	0.66	6.01	6.94	5	1.05	3.67	4.23
	25	3	0.72	5.82	6.72	5	1.10	3.63	4.19
	30	4	0.80	4.81	5.56	6	1.26	3.37	3.89
	35	4	0.86	4.69	5.42	6	1.30	3.20	3.70

### 8A & 10A

Arc	Pressure	Radius	Flow	Precip in/hr		Radius	Flow	Precip in/hr	
	PSI			ft	GPM			■	▲
	--	--	---	---	---	--	---	---	---

45°	20	7	0.18	2.83	3.27	9	0.20	1.90	2.20
	25	8	0.20	2.74	3.16	10	0.23	1.92	2.22
	30	8	0.22	2.65	3.06	10	0.25	1.93	2.22
	35	9	0.24	2.50	2.89	11	0.28	1.92	2.22
	40	9	0.25	2.38	2.74	11	0.30	1.88	2.17
90°	20	7	0.36	2.83	3.27	9	0.40	1.90	2.20
	25	8	0.40	2.74	3.16	10	0.45	1.92	2.22
	30	8	0.44	2.65	3.06	10	0.50	1.93	2.22
	35	9	0.47	2.50	2.89	11	0.55	1.92	2.22
	40	9	0.50	2.38	2.74	11	0.59	1.88	2.17
120°	20	7	0.48	2.83	3.27	9	0.53	1.90	2.20
	25	8	0.53	2.74	3.16	10	0.60	1.92	2.22
	30	8	0.59	2.65	3.06	10	0.67	1.93	2.22
	35	9	0.63	2.50	2.89	11	0.73	1.92	2.22
	40	9	0.67	2.38	2.74	11	0.79	1.88	2.17
180°	20	7	0.72	2.83	3.27	9	0.80	1.90	2.20
	25	8	0.80	2.74	3.16	10	0.90	1.92	2.22
	30	8	0.88	2.65	3.06	10	1.00	1.93	2.22
	35	9	0.94	2.50	2.89	11	1.10	1.92	2.22
	40	9	1.00	2.38	2.74	11	1.18	1.88	2.17
240°	20	7	0.96	2.83	3.27	9	1.07	1.90	2.20
	25	8	1.07	2.74	3.16	10	1.20	1.92	2.22
	30	8	1.17	2.65	3.06	10	1.33	1.93	2.22
	35	9	1.25	2.50	2.89	11	1.47	1.92	2.22
	40	9	1.33	2.38	2.74	11	1.57	1.88	2.17
270°	20	7	1.08	2.83	3.27	9	1.20	1.90	2.20
	25	8	1.20	2.74	3.16	10	1.35	1.92	2.22
	30	8	1.32	2.65	3.06	10	1.50	1.93	2.22
	35	9	1.41	2.50	2.89	11	1.65	1.92	2.22
	40	9	1.05	2.38	2.74	11	1.77	1.88	2.17
360°	20	7	1.44	2.83	3.27	9	1.60	1.90	2.20
	25	8	1.60	2.74	3.16	10	1.80	1.92	2.22
	30	8	1.76	2.65	3.06	10	2.00	1.93	2.22
	35	9	1.88	2.50	2.89	11	2.20	1.92	2.22

## 12A, 15A & 17A

Arc	Pressure	Radius	Flow	Precip in/hr		Radius	Flow	Precip in/hr		Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲	ft	GPM	■	▲	ft	GPM	■	▲
45°	20	11	0.25	1.59	1.84	14	0.39	1.51	1.75	16	0.49	1.46	1.68
	25	12	0.28	1.60	1.85	15	0.43	1.57	1.82	17	0.57	1.60	1.85
	30	12	0.32	1.68	1.95	15	0.47	1.59	1.84	17	0.58	1.53	1.77
	35	13	0.37	1.80	2.08	16	0.52	1.55	1.79	18	0.63	1.49	1.72
	40	13	0.42	1.91	2.21	17	0.57	1.60	1.85	19	0.69	1.55	1.79
45°	20	11	0.50	1.59	1.84	14	0.77	1.51	1.75	16	0.97	1.46	1.68
	25	12	0.55	1.60	1.85	15	0.86	1.57	1.82	17	1.13	1.60	1.85

90°	30	12	<b>0.63</b>	<b>1.68</b>	<b>1.95</b>	<b>15</b>	<b>0.93</b>	<b>1.59</b>	<b>1.84</b>	<b>17</b>	<b>1.15</b>	<b>1.53</b>	<b>1.77</b>
	35	13	0.73	1.80	2.08	16	1.03	1.55	1.79	18	1.25	1.49	1.72
	40	13	0.84	1.91	2.21	17	1.13	1.60	1.85	19	1.38	1.55	1.79
120°	20	11	0.67	1.59	1.84	14	1.03	1.51	1.75	16	1.29	1.46	1.68
	25	12	0.73	1.60	1.85	15	1.15	1.57	1.82	17	1.51	1.51	1.74
	30	12	0.84	1.68	1.95	15	1.24	1.59	1.84	17	1.53	1.53	1.77
180°	35	13	0.97	1.80	2.08	16	1.37	1.55	1.79	18	1.67	1.49	1.72
	40	13	0.98	1.91	2.21	17	1.51	1.60	1.85	19	1.84	1.47	1.70
	20	11	1.00	1.59	1.84	14	1.54	1.51	1.75	16	1.94	1.46	1.68
240°	25	12	1.10	1.60	1.85	15	1.72	1.57	1.82	17	2.26	1.51	1.74
	30	12	<b>1.26</b>	<b>1.68</b>	<b>1.95</b>	<b>15</b>	<b>1.86</b>	<b>1.59</b>	<b>1.84</b>	<b>17</b>	<b>2.30</b>	<b>1.53</b>	<b>1.77</b>
	35	13	1.46	1.80	2.08	16	2.06	1.55	1.79	18	2.50	1.49	1.72
270°	40	13	1.68	1.91	2.21	17	2.26	1.60	1.85	19	2.76	1.47	1.70
	20	11	1.33	1.59	1.84	14	2.05	1.51	1.75	16	2.59	1.46	1.68
	25	12	1.47	1.60	1.85	15	2.29	1.57	1.82	17	3.01	1.51	1.74
360°	30	12	1.68	1.68	1.95	15	2.48	1.59	1.84	17	3.07	1.53	1.77
	35	13	1.95	1.80	2.08	16	2.75	1.55	1.79	18	3.33	1.49	1.72
	40	13	2.24	1.91	2.21	17	3.01	1.60	1.85	19	3.68	1.47	1.70
360°	20	11	1.50	1.59	1.84	14	2.31	1.51	1.75	16	2.91	1.46	1.68
	25	12	1.65	1.60	1.85	15	2.58	1.57	1.82	17	3.39	1.51	1.74
	30	12	<b>1.89</b>	<b>1.68</b>	<b>1.95</b>	<b>15</b>	<b>2.79</b>	<b>1.59</b>	<b>1.84</b>	<b>17</b>	<b>3.45</b>	<b>1.53</b>	<b>1.77</b>
360°	35	13	2.19	1.80	2.08	16	3.09	1.55	1.79	18	3.75	1.49	1.72
	40	13	2.52	1.91	2.21	17	3.39	1.60	1.85	19	4.14	1.47	1.70
	20	11	2.00	1.59	1.84	14	3.08	1.51	1.75	16	3.88	1.46	1.68
360°	25	12	2.20	1.60	1.85	15	3.44	1.57	1.82	17	4.52	1.51	1.74
	30	12	2.52	1.68	1.95	15	3.72	1.59	1.84	17	4.60	1.53	1.77
	35	13	2.92	1.80	2.08	16	4.12	1.55	1.79	18	5.00	1.49	1.72

**Bold = Recommended pressure**